Model No. REP-LGSA

ROHS FC CE

S

0

R



Key features:

- Plug the "Lightning Stop" into any grounded power socket (best in a grounded power socket.)
- All your valuable electronic devices in the same group within 10 meters are protected against indirect lightning strikes, power surges and spikes.
- Surge arrest/2x MOV/1100J/250V/16A/50Hz
- LED indication to see if the Lightning stop is enforced
- Max spike current: 20000 Amps, L-N 10000A, L-G 10000A
- Clamping Voltage: L-N, L-G, 1.5KV
- Protection Modes: L-N, L-G
- Response time: < 1ns
- Max energy dissipation: 1100j
- Nominal AC rating 6A, 250V
- White color housing
- South African version

Accessories:

Blister Packaging

Packaging:





Single

Dual

Certifications:

- · CE-LVD N/A
- · CE-EMC N/A
- ETL N/A
- RoHS N/A
- · Reach N/A

N/A Available for











Clamshell packing: Single Pack

Product Dimensions	H(mm)	W(mm)	D(mm)	NW(kg)	GW(kg)	Quantity per carton			
Product	51.43	45.46	42		0.09	NA			
Gift Box	198.5	135.3	56.8			NA			
Inner Carton						pcs			
Outer Carton	395	205	150		1.28	10 pcs			
Container Loading	20ft	40ft	40ft HQ						
By number of units:	25000	52000							

Clamshell packing: Dual Pack

FOB port:

Product Dimensions	H(mm)	W(mm)	D(mm)	NW(kg)	GW(kg)	Quantity per carton
Product	51.43	45.46	42		0.18	NA
Gift Box	198.5	215	56.8		0.2	NA
Inner Carton						pcs
Outer Carton	395	410	150		2.2	10 pcs
Container Loading	20ft	40ft	40ft HQ			
By number of units:	15000	31000				
FOB port:		SZ				